

TYPE	RATING (KVA)	INPUT VARIATION	OUTPUT ACCURACY %	DIMENSIONS W X D X H (mm)	WEIGHT (kg)
CET- Y-110-B	110	± 15%	± 1 %	800 X 800 X 1900	600
CET- Y-110-C	110	± 20%	± 1 %	800 X 800 X 1900	630
CET- Y-160-B	160	± 15%	± 1 %	800 X 800 X 1900	630
CET- Y-160-C	160	± 20%	± 1 %	1200 X 800 X 1900	800
CET- Y-200-B	200	± 15%	± 1 %	1200 X 800 X 1900	800
CET- Y-200-C	200	± 20%	± 1 %	1200 X 800 X 1900	900
CET- Y-250-B	250	± 15%	± 1 %	1200 X 800 X 1900	900
CET- Y-250-C	250	± 20%	± 1 %	1400 X 800 X 1900	1200
CET- Y-315-B	315	± 15%	± 1 %	1400 X 800 X 1900	1200
CET- Y-315-C	315	± 20%	± 1 %	2400 X 800 X 1900	1400
CET- Y-400-B	400	± 15%	± 1 %	2400 X 800 X 1900	1400
CET- Y-400-C	400	± 20%	± 1 %	2400 X 800 X 1900	1600
CET- Y-500-B	500	± 15%	± 1 %	2400 X 800 X 1900	1600
CET- Y-500-C	500	± 20%	± 1 %	2400 X 800 X 1900	2000
CET- Y-630-B	630	± 15%	± 1 %	2400 X 800 X 1900	2000
CET- Y-630-C	630	± 20%	± 1 %	3000 X 1000 X 2300	2600
CET- Y-800-B	800	± 15%	± 1 %	3000 X 1000 X 2300	2600
CET- Y-800-C	800	± 20%	± 1 %	3200 X 1000 X 2300	2800
CET- Y-1000-B	1000	± 15%	± 1 %	3200 X 1000 X 2300	2800
CET- Y-1000-C	1000	± 20%	± 1 %	3200 X 1000 X 2300	3000
CET- Y-1250-B	1250	± 15%	± 1 %	3200 X 1000 X 2300	3000
CET- Y-1250-C*	1250	± 20%	± 1 %	3800 X 1600 X 2500	4500
CET- Y-1600-B*	1600	± 15%	± 1 %	3800 X 1600 X 2500	4500
CET- Y-1600-C*	1600	± 20%	± 1 %	3800 X 1600 X 2500	6300
CET- Y-2000-B*	2000	± 15%	± 1 %	3800 X 1600 X 2500	6300
CET- Y-2000-C*	2000	± 20%	± 1 %	4500 X 1800 X 2800	7500
CET- Y-2500-B*	2500	± 15%	± 1 %	4500 X 1800 X 2800	7500
CET- Y-2500-C*	2500	± 20%	± 1 %	4500 X 1800 X 2800	8600
CET- Y-3150-B*	3150	± 15%	± 1 %	4500 X 1800 X 2800	8600
CET- Y-3150-C*	3150	± 20%	± 1 %	5500 X 2000 X 3000	9500
CET- Y-4000-B*	4000	± 15%	± 1 %	5500 X 2000 X 3000	9500
CET- Y-4000-C*	4000	± 20%	± 1 %	6500 X 2200 X 3000	10500

(*) : Oil immersed transformer.